



EVDC-180 (EU) Specifications

Accelerating mass adoption of electric vehicles by delivering sustainable fast charging solutions that can be deployed anywhere

EVDC-180 (EU)

180kW DC Fast Charger

FEATURES

- True simultaneous charging - charge two cars at the same time
- Future-proof design with 1000 V max output
- Driver friendly with a 10" LCD touchscreen and simple to use interface
- CHAdeMO and CCS2 or dual CCS2 charging cables
- Ethernet, 4G and Wi-Fi network connectivity
- OCPP 1.6 and ISO 15118 compliant
- Start modes include plug-n-play, RFID card, OCPP and optional POS
- IP54 rated enclosure ideal for a wide range of locations and conditions



SPECIFICATIONS	
Connectors	CHAdeMO + CCS2 or CCS2 + CCS2
Output Power	180 kW (can charge two cars simultaneously at 90 kW each))
Output Voltage	300 - 1000 V
Output Max Current	300 A (0 - 300 A variable range)
Supply Input	400 Vac (+/- 10%)
Supply Frequency	50 Hz
Input Current	265 A (@ 400 Vac)
Grounding Detection	30 mA
Efficiency	≥96% (50%-100% load)
Power Factor	≥0.99
Harmonic Current	<5%
Ripple Voltage	1%
Network Connectivity	Ethernet / 4G / Wi-Fi
Communication Protocol	OCPP 1.6
Charging Cable Length	5 m (16.4 ft)

SPECIFICATIONS CONT..	
Start-up Mode	Automatic charging / RFID card / OCPP
POS (Credit Card Reader)	Optional (enabling card payments)
LCD Display	10 inch touchscreen
Protection	Over / under voltage protection, overload protection, short circuit protection, over / under temperature protection, surge protection, communication failure
IP rating	IP54
Emergency Stop Button	Yes
Cooling Method	Forced air cooling
Operating Temperature	-4°F (-20°C) to 122°F (50°C)
Operating Humidity	5%-95% without condensation
Dimensions (W x D x H)	35.4 x 22.4 x 63.0 (900 x 570 x 1600) inch (mm)
Weight	~428 kg (944 lbs)
Certification	CE, IEC 61851, ISO 15118
MTBF	100,000 hours
Warranty	2 years as standard



EVESCO
(PART OF POWER SONIC CORP.)
NA, LATAM & APAC
365 Cabela Dr Suite 300,
Reno, Nevada 89439
USA

EMEA
Smispol 4, 3861 RS,
Nijkerk
The Netherlands
T: +31 33 7410 700